# PANduo pH® Turboxy





# Simultaneously regulates pH and chlorine levels (ppm)

Suitable for campsites, hotels, residential complexes.





AYPA1216 = Without Avady Connect AYPA1106 = With Avady Connect

POUIS PO

 Live display of the chlorine content in ppm, of the pH value and of the temperature



 Peristaltic pump for pH (1.5L/h)



• Panel dimensions: 58 x 38 x 17 cm



 Peristaltic pump for chlorine (3L/h)





Scan to

- Professional analysis chamber:
  - Turboxy® chlorine sensor
  - pH sensor
  - Flow switch
    - Flw
  - Sampling valve

# **INNOVATIVE**

- PANduo pH Turboxy simultaneously regulates pH and chlorine levels
- Thanks to patented Turboxy® technology, the analysis chamber is compact, making maintenance easier.
- Features an abrasive impeller for stable chlorine measurement.
- The sensor is protected against induced electric currents in the water.

# **SAFE**

- Volumetric alarm preventing the chemical container running dry.
- Dosage proportional to pH and chlorine requirements.
- Jack input connectors for detection of empty pH and chlorine containers.
- The Turboxy® sensor has an integrated flow switch and temperature sensor.

# COMPLETE

• Delivered with a **complete kit** for quick and easy installation :





# **VERSATILE**

- Intended for public pools (up to 90 m³) and private pools (up to 150 m³).
- Compatible with:
  - Organic and inorganic chlorine
  - Stabiliser up to 50 mg/l

# WARRANTY

• Device: two years | pH sensor: one year

# INSTALLATION RECOMMENDATIONS

• At over 30°C, use a B10 impeller (10000019).

# Web AvadyConnect® Interface



By installing the **optional AVADYCONNECT® COMMUNICATION KIT**, this device will allow the user to remotely consult and control pool related data.



**ADVANTAGE** A single dashboard to remotely manage the maintenance of all your pools. You can now remotely change device settings, receive low level of product alerts, check data history and graphs etc.

Discover our web interface at www.avadyconnect.com; username and pw: demo

AYAC100524



# PANduo pH® Turboxy

# Simultaneously regulates pH and chlorine levels (ppm)

Suitable for campsites, hotels and residential complexes.







• Live display


of the **chlorine content in ppm**, of the **pH value** and of the temperature







 Peristaltic pump for pH (1.5L/h)





 Peristaltic pump for chlorine (3L/h)



- Professional analysis chamber:
  - Turboxy® chlorine sensor
  - pH sensor
  - Flow switch
  - Sampling valve

# **INNOVATIVE**

- PANduo pH Turboxy simultaneously regulates pH and chlorine levels
- Thanks to patented Turboxy® technology, the analysis chamber is compact, making maintenance easier.
- Features an abrasive impeller for stable chlorine measurement.
- The sensor is protected against induced electric currents in the water.

# **SAFE**

- Volumetric alarm preventing the chemical container running dry
- Dosage proportional to pH and chlorine requirements
- Jack input connectors for detection of empty pH and chlorine containers
- The Turboxy® sensor has an integrated flow switch and temperature sensor.

# **VERSATILE**

- Intended for public pools (up to 90 m³) and private pools (up to 150 m³)
- Compatible with:
  - Organic and inorganic chlorine
  - Stabiliser up to 50 mg/l

# WARRANTY

• Device: two years | pH sensor: one year

# **INSTALLATION RECOMMENDATIONS**

• At over 30°C, use a B10 impeller (10000019)

# • Supplied with a complete kit for quick and easy installation: X4 DN50 DN63 Sonde Turboxy BREVET EUROPEEN

# AvadyConnect® Web Interface



Device predisposed to receive the **AVADYCONNECT® option** to remotely consult and control pool related data.



**ADVANTAGE** A single dashboard to remotely manage the maintenance of all your pools. You can now remotely change device settings, receive low level of product alerts, check data history and graphs etc.

Discover our web interface at www.avadyconnect.com; username and pw: demo

AVA C100202



AYPA1016