



Physico pH® Turboxy



Simultaneously regulates pH and chlorine levels (ppm)
Suitable for campsites, hotels, residential complexes, etc...



AYPA1202



Scan to discover !



• **pH** output :
230 Vac pre-powered output socket



• **Chlorine** or Bromine output:
230 Vac pre-powered output socket



• Panel dimensions:
58 x 38 x 17 cm

• Professional analysis chamber:
- Turboxy® chlorine sensor
- pH sensor
- Flow switch **Flw**
- Sampling valve

INNOVATIVE

- Physico pH® Turboxy simultaneously regulates pH and chlorine levels.
- Display of water temperature.
- Thanks to patented Turboxy® technology, the analysis chamber is compact, making maintenance easier.
- Features an abrasive impeller for stable chlorine measurement.
- The sensor is protected against induced electric currents in the water.

COMPLETE

- Delivered with a **complete kit** for quick and easy installation :



VERSATILE

- Intended for private and public pools up to 15 to 1500 m³.
- Compatible with:
 - Organic and inorganic chlorine
 - Stabiliser up to 40 mg/L

SAFE

- Volumetric alarm preventing the chemical container running dry.
- Dosage proportional to pH and chlorine requirements.
- Jack input connectors for detection of empty pH and chlorine containers.
- The Turboxy® sensor has an integrated flow switch and **temperature sensor**. **T°**

WARRANTY

- Device: two years | pH sensor: one year

AvadyConnect® Web Interface



By installing the **optional AVADYCONNECT® COMMUNICATION KIT**, this device will allow the user to remotely consult and control pool related data.



ADVANTAGE A single dashboard to remotely manage the maintenance of all your pools. You can now remotely change device settings, receive low level of product alerts, check data history and graphs etc.

Discover our web interface at www.avadyconnect.com; username and pw: demo

AYAC100524